Edgewood Ave 6000 S OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION 12 TOWNSHIP 14 RANGE 4 DATE: 9-21-04 PARTY CHIEF: Wilcoxen Points CREW: \_ TYPE OF MARKER: Broken Harrison METHOD OF ESTABLISHMENT: \_\_\_\_County: 7-29-99 F. < @ IN. S.P.C. E ZONE NAD '83 14041202 NAME: 492197.9166(m) N: 68406.2351(m) E: Edgewood Ave 6000 S 86.60 PWP

Original post set 1820 by Hendricks with witness: 14" beech S 45 E 11 links; 11" beech N 36 W 26 links per Marion County Atlas pg. 9. Hosbrook 11-27-1849 called same witness per Franklin Township Legal Survey Book pg. 22. 7-28-64 called pipe over stone. 7-12-75 called railroad spike over stone 8" down. Excavated 5-16-88 stone found 10" down. Set Harrison. Re-tied by Kiste 7-29-99. Re-tied 9-21-04 by Wilcoxen. 14041202

1	+U412U2	er en
REF.	DISTANCE	DESCRIPTION
1.	19.42'	Mag nail w/brass washer NE PwP#833-1387 4"up
2.	89.50'	Mag nail w/brass washer NE PwP#8331-38701 10"up
3.	17.00'	Road nail (bent) W fence post 8"up
4.	86.60'	Mag nail w/brass washer N PwP 186-738 6"up
5.	56.75'	PK nail w/washer SW 20" maple spur root